

Page 9, line 2, after "is", insert -- disposed below the main actuation mechanism 22 and substantially between the links 36 of the arm member 16 and --;

line 4, after "18.", insert the following new sentence -- The auxiliary actuation mechanism 24 is also located between the main frame 12 and the pivotal connection 47 of the tine mounting member 18 to the support arm 16 and adjacent to a second side of the pivotal connection 47 being substantially opposite from the first side thereof where the tines 20 are located. --; and

line 15, after "16.", insert the following new sentence -- As is clearly apparent in FIG. 5, by the arm member 16 extending a substantially greater distance outwardly from the main frame 12 than the support member 14 extends from the main frame 12, the tines 20 can be positioned at a location spaced forwardly from the support member 14 so as to enable the support member 14 and tines 20 together to grasp and support the object T located therebetween for relocating the object T upon maneuvering of the apparatus 10 by operation of the material handling vehicle without the support member 14 having to extend sufficiently under the object T to alone support the object without assistance from the tines 20. --.

In the Claims:

Please rewrite Claim 1 as follows:

1. (amended) An apparatus for grasping odd-shaped objects to relocate the same, comprising:

(a) an elongated upright main frame having opposite upper and lower ends, said main frame [being attachable] having means for attaching said main frame to a material handling vehicle for maneuvering said main frame between different heights and locations by operation of the material handling vehicle;

(b) a support member mounted to said main frame adjacent to said lower end thereof and being adapted for engaging an edge of an object, said support member extending outwardly from said lower end of said main frame through a first distance;